

Data sheet

Gutleutstrasse, Frankfurt Highly connected, premium datacentre space





TelecityGroup Gutleutstrasse 310 60327 Frankfurt/M. Germany



General

Gross Data Floor Area (m2) - 10000

Building type - Purpose-built datacentre

Building tenure - Long term lease

Number of data floors - 4

Number of IT zones - 12

High density capacity - Yes
Minimum floor load capacity (kg/m2) - 2000

Raised access floor height (mm) - 680

Raised floor to ceiling height (metres) - 4.5-11

Goods lift maximum load (tons) - 1.0

Separate delivery bay - Yes

Build/unpacking room - Yes

Security

Type of security system - Proximity Access Card

Staffed - 24/7/365

Fire Detection & Suppression

High sensitivity smoke detection system - Yes

Type of fire suppression system - Inergen gas

Smoke detection double knock - Yes

Air Conditioning & Cooling

Type of cooling system - Chilled water

Number of chillers (if applicable) - 6

Maximum cooling capacity (MW) - 10.3

 $\begin{tabular}{ll} \textbf{Cooling redundancy each independent system -} \ N+1 \\ \end{tabular}$

CCUs or in-row cooling - CCU

Power

Number of independent supplies into site - 4

Total incoming feed capacity (MVA) - 14.4

Diverse power route - Yes

Generator fuel at full load (hours) - 24

UPS type - Hybrid Rotary

UPS autonomy (minutes) at full system load - 10

Maximum UPS capacity (kVA) - 12500

UPS redundancy - N+1, 2N optional

Generator redundancy - N+1, 2N optional

Maximum Generator capacity (MVA) - 19.2t

Find out how we can help your business, call **0845 119 9911**

